



- ① PVC SCH 40 1/2" SLIP X 1/2" FNPT ELBOW
- ② PVC INSERT ADAPTER TO .670 OD DRIP LINE, DIG C/N 15-067 (COLOR BROWN)
- ③ PVC SCH 80 1/2" RISER (LENGTH AS REQUIRED)
- ④ PVC SCH 40 STREET ELBOW
- ⑤ PVC SCH 40 3/4" X SLIP X 1/2" FNPT TEE
- ⑥ PVC SCH 40 SYSTEM LATERAL INLET PIPE
- ⑦ PVC SCH 40 1/2" SLIP TEE
- ⑧ PVC SCH 40 1/2" SLIP ELBOW
- ⑨ PVC INSERT ADAPTER TO .670 OD DRIP LINE, DIG C/N 15-067 (COLOR BROWN)
- ⑩ EXCEL™ .670 OD (17 MM) PC DRIP LINE
 - i (.670 OD 17 MM) AX-XXP
COLOR BROWN
 - ii (.670 OD 17 MM) AX-XXP-CV
WITH CHECK VALVE, COLOR BROWN
- ⑪ PVC SCH 40 1/2" SLIP CAP
- ⑫ 3/4" FNPT FLUSH VALVE, (DETAIL SEE FILE #11)
 - i FLUSH VALVE WITH 3/4" FNPT, DIG C/N 18-038 WITH OPENING PRESSURE OF 3 PSI. COLOR BLACK
- ⑬ 1/2" MNPT AIR VACUUM RELIEF VALVE, PLACED AT THE INSTALLATION'S HIGHEST SPOT, DIG C/N 18-028. MAY NEED TO ADD MORE THAN ONE UNIT. (DETAIL SEE FILE #10)

8

EXCEL .670 OD (17 MM) PC DRIP LINE FOR SUBSURFACE INSTALLATION
 CLOSED LOOP SIDE FEED LAYOUT FROM A 1/2" RISER (PARKING ISLAND)